

ARCHITECTURAL

GRATES + DRAINS

Code 250Custom-304-C

Category Custom Made

Recessed Channel

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

40mm Minimum

250mm Maximum

Grate Style CR

Steel Grade 304

dimensions

Range Custom Fabrication



250Custom-304-C **Linear Drain**

304 stainless steel 250mm wide grate and custom channel depth.

Depth between 42mm and 260mm.

Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish

Suits Load Class C.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency

SPECIFICATIONS + DIMENSIONS

Channel Width **Channel Depth** Length(s) **Outlet Size**

260mm 42mm - 260mm As Required DN40, DN50, DN65, DN80, DN100

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage**

Phone 1300 653 403

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 20/05/2024 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.